

t2MonoFit®

Guide for a successful installation

Before you install your new T2 integrated tap, there are a few things to bear in mind for a successful installation.

Consider water, waste, power and space.

Full installation instructions and cutting templates are provided in the product manual.

Capacity	Chilled 50 L/hr 80 L/hr
Temperature	Chilled 2°C
Dispense height	310mm
Power	230-240V
Dimensions	Tap W160 x D324 x H407mm Undercounter W320 x D430 x H390mm
System	ProCore® DryChill®
Technology	EcoMode DeepSparkle® (select models only)
Hygiene	Totality®

Minimum
clearance
338mm.

Tap hole cutout
60mm.

Use cutting template
provided in box.

60mm

10A*
power supply.
Single socket
within 2m of unit.
*Earth leakage
protected

Mains waste
connection.
or Bluetooth®
Waste Kit

Mains supply
potable water.
0.05MPa (0.5 bar)
min pressure,
within 2m of unit.

min 500mm

min 500mm

min 500mm

300mm

30mm

45mm

Vent kit cutout
300 x 30mm.
Allow clearance of
45mm each side.
Cutting template
available.

T2 MonoFit® Cutting Template

SimpleFit® Vent Kit Cutting Template

borg&
overström

For support please contact



+44 (0)1362 695 006



support@borgandoverstrom.com

VIEW T2
MANUAL



t2 MonoFit®

Guide for a successful installation

Once your T2 MonoFit® integrated tap is installed, you will need to commission the hot tank and sanitise prior to first use.

Full operation and sanitisation instructions are provided in the product manual.



Securely fasten the drip tray using brackets provided.

Chilled inlet AP3 carbon filter.
Allow access for replacement.

CO₂ cylinder with regulator.
4 bar pressure (58 PSI)
Allow access for replacement.

SimpleFit® Vent Kit

Ensure there is free flow of air for ventilation.

borg &
overström

For support please contact



+44 (0)1362 695 006



support@borgandoverstrom.com

VIEW T2
MANUAL

