

t2

Drink differently with digital precision and freshly-filtered water on tap.



Overview

- Transformative technology.
- Premium aesthetic.
- Powerful and energy-efficient.
- Intelligent energy-efficiency
- Hygiene assurance in every pour.
-

Specifications

Chilled temperature - 2°C
 ProCore+ chilled & sparkling capacity - 80L/h
 ProCore chilled & sparkling capacity - 50L/h
 Dispense height - 310
 Tap height - 390

Accessories

[500ml water bottles](#)
[Printed paper cups 463428](#)
[Install kit with 3M filter 461202](#)
[Refill station cabinet 601604](#)

Tap: W160xD324xH390mm

T2 ProCore ProCore: W320xD375xH335mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	Z42000	Z42010	Z42020	Z42030
Chilled & Sparkling	Dry Chill®	200W	Z42080	Z42090	Z42100	Z42110
Chilled, Ambient & Sparkling	Dry Chill®	200W	Z42160	Z42170	Z42180	Z42190

Tap: W160xD324xH390mm

T2 ProCore+ ProCore: W320xD375xH350mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	Z42240	Z42250	Z42260	Z42270
Chilled & Sparkling	Dry Chill®	200W	Z42320	Z42330	Z42340	Z42350
Chilled, Ambient & Sparkling	Dry Chill®	200W	Z42400	Z42410	Z42420	Z42430
Simple-fit Ventilation Base W322xD431xH60mm (Includes 20mm overhang)						

borg&
overström

Find out more:

<https://www.borgandoverstrom.com/en/p/tap-systems/t2/>