

borg &
overström



A simple-fit font for effortless,
non-invasive tap installation.

t3 MonoFit®

t3 MonoFit®

Easy-fit elegance for T3 integrated taps,
delivering maximum impact with minimal cutting.

Designed to minimise work surface cutting, the T3 MonoFit® font ensures easy and convenient installation with a small, standard-size, single service hole.

At a glance.

Water options



Configuration



Colour



System

ProCore®

Powerful and compact, energy-efficient modular system.

DryChill®

Rapid and hygienic, efficient chilling technology.

Technology

EcoMode

Energy-saving technology.

DeepSparkle®

Sparkling water with long-lasting fizz.

Viovantr® (optional)

Chemical-free, eco-friendly integrated UV-LED purification.

Hygiene

Totality®

Filtration and hygiene assurance.

Effortless installation.

The T3 MonoFit® provides a versatile solution for simple, straightforward installation into virtually any material. The innovative design eliminates the necessity for specialised cutting whilst the non-destructive fixings maintain a secure, watertight seal with the surface below.

One size fits all.

Engineered with precision, the T3 MonoFit® minimises countertop cutting by 90%, enabling all services to be seamlessly installed through a single, standard-sized 60mm hole.

Simplicity at its best.

With a single 60mm circular drilled worktop hole, unique Simple-fit Ventilation and the option for Bluetooth® Alarmed Waste, this is simply the easiest way to install a premium tap system into your breakroom.

Upgrade in an instant.

Providing a simple solution for upgrading previous integrated tap installations, the T3 MonoFit® can be placed neatly over previously made cut-outs, allowing a quick and easy upgrade to any environment.



T3 MonoFit® font
Circular cutout
60mm diameter.



90%
smaller
cut out



T3 regular font
Rectangular cutout
146mm x 311mm.



t3 MonoFit®



Chilled



Sparkling



Ambient



Hot



The detail.

Capacity ProCore	Chilled 80 L/hr	Sparkling 80 L/hr	Hot 16 L/hr
Temperature	Chilled 2°C	Sparkling 2°C	Hot 96°C
Dispense height	310mm Perfect for filling water bottles, glasses or carafes		
Power	230-240v		
Dimensions	Integrated Tap W160xD324xH350mm	Undercounter ProCore Unit W320xD470xH390mm	



Optional accessories.

Deep Sparkle® CO₂ Refills

Can be disposed via standard steel recycling or general waste. Requires CO₂ regulator with gauge.



Bluetooth® Alarmed Waste Kit

A device that emits an audible alarm at high water level and sends a signal via Bluetooth® to deactivate the control panel.


Place an order.

+44 (0)1362 696 006
sales@borgandoverstrom.com

Excellence in every pour.

 **Totality® hygiene assurance** in every pour.

 **UK designed and built** with nearshore supply.

 **Bottleless and sustainably conscious.**

 **ProCore® advanced modular technology.**