

# t3 MonoFit®

## Guide for a successful installation

Before you install your new T3 MonoFit® integrated tap, there are a few things to bear in mind for a successful installation.

Consider water, waste, power and space.

Full installation instructions and cutting templates are provided in the product manual.

Capacity	Chilled 50 L/hr 80 L/hr Hot 16 L/hr
Temperature	Chilled 2°C Hot 96°C
Dispense height	310mm
Power	230-240V
Dimensions	Tap W160 x D324 x H338mm Undercounter W320 x D471 x H400mm
System	ProCore® DryChill®
Technology	EcoMode DeepSparkle® (select models only)
Hygiene	Totality®

Minimum  
clearance  
338mm.

Tap hole cutout  
60mm.

Use cutting template  
provided in box.

60mm

10A\*  
power supply.  
Single socket  
within 2m of unit.  
\*Earth leakage  
protected

Mains waste  
connection,  
or Bluetooth®  
Waste Kit

Mains supply  
potable water.  
0.05MPa (0.5 bar)  
min pressure,  
within 2m of unit.

min 500mm

min 500mm

min 500mm

300mm

30mm

45mm

Vent kit cutout  
300 x 30mm.  
Allow clearance of  
45mm each side.  
Cutting template  
available.

T3 MonoFit® Cutting Template

SimpleFit® Vent Kit Cutting Template

borg&  
overström

For support please contact



+44 (0)1362 695 006



support@borgandoverstrom.com

VIEW T3  
MANUAL



# t3 MonoFit®

## Guide for a successful installation

Once your T3 MonoFit® integrated tap is installed, you will need to commission the hot tank and sanitise prior to first use.

Full operation and sanitisation instructions are provided in the product manual.

